

TITLE

AUTOMATIC WINDOW SYSTEM FOR SAVING ENERGY, ACHIEVED BY USING SUN ENERGY DURING THE COLDER SEASON, BY CONTROLLING THE SOLAR RADIATION DURING THE SUMMER, THE THERMAL INSULATION, AS WELL AS CONTROLLED INCIDENCE OF LIGHT INTO THE INSIDE OF THE BUILDING AND A CONTROLLED EXCHANGE OF AIR ENERGY SAVING WINDOW SYSTEM

FIELD OF THE INVENTION

[0001] The present invention relates to window systems. More particularly, the present invention relates to an automatic window system for saving energy which employs sun energy during the colder season, controlled solar radiation during the warmer season, thermal insulation, controlled incidence of light into the inside of the building, and controlled air exchange.

DESCRIPTION BACKGROUND OF THE INVENTION

[0002] The state of the art for different advancements, e.g. energy saving windows is described in different documents, such as patents DE 296 24 245 U1 [1] and EP 0978617B1 and includes designs, which enable on the one hand a mechanism for the parallel opening of the window casement or, on the other hand, the use of sun energy during the winter, e.g. for example, as in patent IT 01/00026.

BRIEF SUMMARY OF THE INVENTION

[0003] The present invention has the object of creating pre-conditions, which are necessary for an efficient control of the climate and temperature of a building, which is decisively primarily influenced through the presence of glass surfaces in the building. This is guaranteed through the application of The object of the present invention is achieved through a window design, which uses simple components and mechanisms.

[0004] In one embodiment, the window system consists of a frame, which also fulfils the function of supports a frame and a counter-frame of the window and/or is part of the support

frame of the building, an outer and an inner window casement, which are glazed and, ~~in themselves, are independent of each other, as well as~~ and a mechanism with the characteristic of for opening and closing the above-named window casements independently of each other. Each of these two window casements consists of a profile with a variable heat transition efficient of preferably $U = 0.8$ to $0.6 \text{ W/m}^2\text{°K}$.

[0005] The ~~outside-outer glass pane~~ pane consists of ~~insulated~~-insulating glass with suitable physical and optical characteristics, a variable heat transition efficient of preferably $U = 1.6$ to $1.1 \text{ W/m}^2\text{°K}$, as well as a variable transparency coefficient of preferably 68% to 77% with ~~the a~~ corresponding transmission of sun energy. ~~In the inside of~~ Inside the outer insulating glass pane is a blind or a type of curtain on rolls, consisting of a material with variable thermal conductivity of preferably $\lambda = 0.014$ to $0.0126 \text{ W/m}^2\text{°K}$. The blind, ~~as well as~~ and the curtain are driven by a motor. The inner glass ~~insulation~~-pane consists of insulating glass with suitable physical and optical characteristics, and has a variable heat transition coefficient of preferably $U = 0.6$ to $0.3 \text{ W/m}^2\text{°K}$. For both individual insulating glass ~~units~~panes, ~~there are~~ spacers ~~required~~are foreseen which – ~~compared in comparison~~ to other systems - change the thermal conductivity ~~in such a way, that it is possible to achieve better insulation along the perimeter of the insulating glass pane.~~

[0006] The ~~entirety of the illustrated solutions presents~~ features described herein provide a window system, which – depending on the external climatic conditions – creates a better indoor climate. ~~Usually, it is as follows: that~~ One mode of operation of a window according to the present invention is as follows: during the wintertime, when the sun shines on the glass surfaces of a building, the outer window casing with the movable blind or the rolled up curtain stays closed, while the inner window casing can be opened parallel to the outer window casing towards the inside. The sun's energy of the sun, which enters the building through the outer insulated glass pane, first ~~of all~~ warms up the inside of the window and then, ~~via~~ by convection, warms up the air near the glass surface and, in turn, the entire room. One part of the sun's energy goes straight through both glass surfaces, which ~~inevitably~~ warms up the room ~~in a direct way~~ directly.

[0007] During the summer, ~~and in order to control the solar radiation~~, the inner window casement stays closed to guarantee the provide insulation, and the outer window casement - with the blind or the curtain rolled down – will be opened to the outside. ~~In this~~ This way, the open

window casement forms a barrier against the solar radiation. The separation of the outer and inner glass panes enables the direct and complete release of heat, which is collected on the outside glass pane, to the air on the outside, so that the inner insulated glass pane warms up.

[0008] The heat insulation of the window is at its best, when both window casements - with the blind or the curtain down - are fully closed and as far as the circumstances allow, the previously described ~~measures are carried out~~ mode of operation is implemented. The fact ~~that~~ When the blind or the curtain are down, ~~makes it possible to improve and guarantee the~~ thermal insulation of the outer insulated glass pane can be improved.

[0009] During the cold season and when both window casements are closed, ~~the window~~ insulation can be improved ~~through the following solution, which influences the by altering~~ thermal conduction inside the window casements. ~~The above-mentioned solution is intended for the installation in a pipeline~~ This involves installing a conduit along an inner side wall, ~~and~~ visible between both insulating glass units. This pipeline contains a liquid, which is normally used ~~in for~~ heating and cooling ~~elements purposes~~, and ~~has two connecting parts in two places, which run~~ runs through the frame. This application is ~~only justifiable appropriate~~ if the energy necessary for it ~~it~~ can be taken from known or renewable energy sources, e.g. from the storage of a solar unit or from passive existing heat sources from pipelines underneath the ground, or from below the building where ~~as it is known there are~~ there may be liquids of suitable temperatures and quantities, or from a combination ~~of both possibilities thereof~~. This solution design warms up the air between both insulating glass casements, which results in a better insulation of the inner insulating glass casement and of the surrounding components of the window.

[0010] Therefore, the contribution of ~~the solar energy~~, which is necessary to change the thermal flow of the insulating glass ~~units~~ panes, depends also on the ~~thermal transition~~ coefficients of thermal conduction of the ~~glazes~~ inner and outer casements containing the glass panes when these are closed or ~~the existence of such conditions, which are required by providing the necessary conditions for the desired thermal flow to occur~~. The ~~air exchange of air is~~ achieved by ~~the fact~~ opening, that for a certain period of time, one window casement opens to the outside and the other towards the inside of the building. The incidence of light is controlled by the motor-driven blind and/or the relevant curtain on rollers inside the inner insulating glass unit. All possible positions of both window casements (open / closed) are programmable; so are the

climate data, which is received via sensors on the inside and outside of the windows. The processed data is also used for ~~the control mechanism for~~ manoeuvring the control mechanism to the required positions.

In the following, the invention is described in an example using the enclosed illustrations, which are:

FIG 1—a front view of the windows with the relevant frame, casements, motor shaft, driving motors, levers, connecting bars and multiple hinges;

FIG 2—a B-B sectional view of the windows with the above-mentioned window casements, levers, multiple hinges in an open position, as well as levers and multiple hinges in a closed position, shown through a broken line;

FIG 3—a A-A sectional view of the mentioned frames or counter-frames, window casements, inner and outer glass with special connection profile between the glass surfaces and the casements, parts of the moving mechanism and parts of the components controlling the thermal flow;

FIG 4—a view of the levers and their connection due to connecting rods;

FIG 5—a view of the levers and their connection via parallel arranged ropes or profile rods;

FIG 6—a view of the levers and their connection via toothed racks;

FIG 7—a view of two lever systems and their connection via parallel arranged ropes or profile rods:

[0011] One ~~particular feature of the windows~~ a window according to the present invention is that the frame and the window casements are completely ~~arranged-disposed~~ on the inside of the window, between the insulating glass panels. Therefore, ~~the~~ heat conductivity, which is ~~influenced through~~ affected by the frame and the window casements, is increased, because ~~they~~ these components are covered through enclosed between the insulating glass panels, which adds to the insulation through the glass panels ~~to the specific insulation of the frame and of the window casements~~.

[0012] ~~For better and total~~ To maximize energy saving, ~~plus maximum and~~ insulation, through covering the frame and the window casements through glass panels, ~~the~~ a ventilator mechanism is placed inside the unit and is visible between both the two window casements. ~~This solution enables the homogeneity of~~ In this embodiment, the entire perimeter, the frame parts, the

window encasements and the glass panels have a more homogeneous temperature, without superimposed mechanisms for the automatic opening of the window panels. Also through ~~the~~Furthermore, by positioning ~~of the~~ pipelines for the warming up and/or cooling down of the inside of the windows, which ~~is are also~~ are also visible through both glass panels, the homogeneity of the-frame parts, window casements and glass panels are not impaired retain a homogeneous structure. A ~~further aspect of~~Even more energy saving is achieved ~~due to by~~ using electric engines, which ~~consume only a little electricity~~have a low energy requirement.

[0013] ~~This solution requires~~The present invention involves the use of multiple hinges, which hold the weight of the window casement during the opening and closing phase, which otherwise would be ~~carried-actuated~~ carried-actuated by the electric engines, ~~in order to keep down thereby~~ minimizing electricity consumption.

DETAILED DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0014] In the following detailed description, the invention is described in detail with reference to different embodiment and to the figures, in which:

[0015] FIG 1 is a front view of an embodiment of a window according to the present invention;

[0016] FIG 2 is a longitudinal cross-sectional view of the window of FIG. 1;

[0017] FIG 3 is a lateral cross-sectional view of the window of FIG. 1;

[0018] FIG 4 is a front view of the levers and connecting rods in one embodiment of the invention;

[0019] FIG 5 is a front view of the levers and connecting ropes or profile rods in another embodiment of the invention;

[0020] FIG 6 is a front view of the levers and connecting toothed racks in still another embodiment of the invention;

[0021] FIG 7 is a front view of lever systems and connecting ropes or profile rods in yet another embodiment of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[0022] The frame of a window in an embodiment of the invention consists of a rolled I (Fig 3; 2; 1) 10 or U profile, which stretches over the entire perimeter. The profile is designed to incorporate the complementary volume formed into the resulting hollow space, which is restricted by the configuration as a I or U or the configuration as a L, C or T. The I profile has to ~~fulfill~~ the task of the frame and of the counter frame and can also represent the support structure of the building. A hollow space of the I profile, in which there is a window casement (Fig 3; 2) 11, is disposed towards the outside of the building, which ~~as a opening~~ forms the entire outside of the window. The outer insulating glass (Fig 3; 2) 14 with the motor-driven blind (Fig 2) 15 in the inside, is fixed with a special profile onto the window casement (Fig 3; 2; 1) 12. The result is that the outer insulating glass conceals the window casement and the window casement conceals the frame. Opposite and symmetrical, inside the hollow space of the I profile, is a window casement, which forms the entire inside of the window (Fig 3; 2; 1) 11; 11a. The inner insulating glass (Fig 3; 2) 13 is linked to the window casement by a special profile (Fig 3; 2) 12. This enables the inner insulating glass to conceal the window casement and the window casement conceals the frame. The inner window casement forms a unit consisting of two components: one part functioning as a frame (Fig 3; 2) 11 and on the other side (Fig 3; 2; 1) 11a, with insulating glass, the opening part of the window. If the inner window casement is completely opened manually, it enables cleaning of the inner glass panels, access to the opening mechanism, the direct release of the solar energy into the room, a better light transmission, as well as an increased exchange of air, in case the outer window casement has also been opened.

[0023] All window casements are provided with suitable safety mechanisms and standard catches and gaskets. For the manually opened window casement, a simple opening and closing mechanism is intended to be used, which has not been graphically illustrated. It should consist of snap-in pins and a holding lever, which are fixed to the specific profile in a suitable place.

[0024] The mechanism of the automatic window system consists at least of: two independent drive shafts (Fig 3; 2; 1) 16, two independent driving motors (Fig 3; 2; 1) 17, eight levers of the same size (Fig 3; 2; 1) 19; 20 plus four connecting rods (Fig 3; 2; 1) 21, four multiple hinges (Fig 2; 1) 30-31, which support the weight of the outer and inner window casements. The drive shafts

(Fig 3; 2; 1) 16 end on both sides in a holder (Fig 3; 1) 22, which is supplied with a receptacle, in order to permit movement in the shafts in both directions. The holders 22 are fixed to the frame.

[0025] The drive shafts with the ability to move independently (Fig 3; 2; 1) 16 are arranged in parallel. Each drive shaft is fixed firmly to two levers, (Fig 1; 2; 3) 19. The rotation surface runs at right-angles to the axle of the drive shaft. An independent driving motor 17 is connected to each drive shaft (Fig 1; 2; 3), which is fixed to the frame. From the frame or the counter-frame to the drive shaft, the order of components is as follows: on one end is the holder of the drive shaft, which is connected to the frame; the opening lever, which is connected to the driving shaft, as well as the driving motor, which is connected to the continuous drive shaft.

[0026] All levers have three different openings on the surface of the rotation level. Two openings are in one place, defined here as at the lower end of the lever, and one opening at the upper end. ~~Four~~ In four of these levers (Fig 3) 19, two for each drive shaft, ~~serve for one of one~~ of the two openings at the lower end of is used for coupling to the drive shaft (Fig 1; 2; 3; 4) 19 and the other, second opening ~~serves is used~~ for fixing a rotating pin 23, to which a connecting rod 21 is connected in order to transmit movement. From the remaining four levers, defined here as auxiliary levers (Fig 1; 2; 4) 20, one of the two openings at the lower end serves for fixing a rotating pin 24, which is connected to a rotating bracket, which in turn is connected to one of the frames. The other, second opening is used for fixing a rotating pin 23, which in turn is fixed to the connecting rod 21.

[0027] On each of the connecting rods, ~~on at~~ each of their ends, at right-angles to the moving direction of the connecting rod, there is a pin. The connecting rod ~~determines provides the~~ coupling of both levers (Fig 1; 2; 4) 19; 20. ~~The One~~ end of the connecting rod is connected with the lever 19, which in turn is connected to the drive shaft 16. The other end is connected to the auxiliary lever 20. The connecting rods (Fig 1; 2; 3; 4) 21, two each for one window casement and ~~on the side positioned to the vertical side of~~ disposed vertically in relation to the windows, transmit the movement of the levers, which are connected to the drive shaft and to the auxiliary levers, which are controlled from the end of the connecting rods through rotating pins 23. This is made possible by starting the movement of opening lever (which is connected to the drive shaft) through the driving motor. This ~~results in generates~~ a rotating movement of the drive shaft. The opening levers move the auxiliary levers and create the same rotating movement of the auxiliary levers around the ~~swivel fixed pivot bracket~~ rotating pin (Fig 1; 2; 4) 24.

[0028] As an alternative to connecting rods, the connection for the opening/closing levers can be ~~done~~ achieved as follows:

[0029] - (Fig 5) Via parallel arranged ropes or profile rods 37; 38. At the lower end of the lever 19; 20 and near the rotation centre, there are two openings. They are situated in specific places along the surface of each lever. Inside the openings, there are parallel positioned ropes or profile rods 37; 38, which are connected to the lever via rotation pins 35; 36. ~~The result makes it possible to transfer~~ As a result, the movement of the drive shaft lever 16 can be transferred onto the auxiliary lever 16. This happens through the tension / pressure of the ropes or profile rods 37; 38 during the rotating phase of the lever in both directions around ~~the swivel, fixed pivot bracket 16; drive shaft 16 and rotating pin 24.~~

[0030] - (Fig 6) Through a system consisting of toothed rack and pinion 39.

[0031] Using the position of drive shaft 16, keeping its relevant storage, and with gear 17, a pinion gear 40 is fixed to the lever of the drive shaft 16. The drive shaft 16 runs through lever 19 and the pinion gear 40. On the opposite side, an identical ~~toothed wheel~~ gear 40 is fixed to the auxiliary lever 20. The auxiliary lever 20 and the toothed wheel are fixed to the frame with a rotating pin 24. The toothed rack is fixed to the frame by special holders 41, which make shifting and a feed motion of the toothed rack possible, in both directions along the connecting rod. ~~The toothed rod does not incorporate any amendments of the systematic construction and the amounts as arranged for the connection rods.~~ The toothed rod ~~clicks~~ couples on the one side into the pinion gear of the drive shaft lever and on the other side into the pinion gear of the auxiliary lever. The driving motor brings forth a rotating motion of the drive shaft, which begins to move the pinion of the drive shaft lever and ~~results in~~ causes a movement of the toothed wheel along its own axle. This results in the movement of the pinion gear of the auxiliary lever 20, which is transferred to the lever 19 ~~of the swivel fixed pivot bracket~~.

[0032] ~~Without exemption, all~~ All levers (Fig 1; 2; 4) 19; 20 have an opening ~~on their upper/near one end, on the same place relating to~~ at the rotation centre. Inside this opening there is a rotating pin 25, which is connected to a ~~sledge bracket~~ 26. Both are connected to the lever. The ~~sledge bracket~~ is intended for a sliding movement in a guide block 27. The guide blocks 27 are fixed to the sides of the window casements and near the ~~sledge bracket 26 and~~ are connected to the relevant levers.

[0033] According to an alternative design style of the ~~sledge-bracket~~ and ~~of~~ the guide block (Fig 5; 6), a moving ~~roll-roller~~ 42 is ~~provided~~~~put in~~, which is movable along a profiled guide block 43, fixed on both ends to the two holders 44 on the window casements[[44]].

[0034] In order to guarantee the feed motion of the window casements on parallel levels and at right-angle to the level of the frame, ~~the solution offers~~~~the present embodiment includes~~ an auxiliary mechanism, which consists of multiple hinges (Fig 1; 2) 30-31. The drive shaft, set in motion by the driving motor, moves in both directions around its axle and results in the movement of ~~the~~ four levers, of which ~~there are two~~ are fixed to the drive shaft and two are auxiliary levers. Through the force produced by the levers (Fig 1; 2; 4) 19; 20 and ~~put~~ transmitted onto the ~~sledge-bracket~~ 26, the ~~sledge-bracket moves~~26 moves on the guide blocks 27 and at the same time the ~~centre-centers~~ of the openings, which are at provided the upper ~~end-ends~~ of the lever on the opposite side of the rotating axes of the levers, move ~~on a parallel level to themselves-outwards and keep the while maintaining a parallel position on the level of their relation to the~~ window casements. This solution makes it possible to move the window casement a little at a time and, thus, to open / close the window casement, either independently or both at the same time.

[0035] The support mechanism (Fig 1; 2) for the opening of the window casement requires four multiple hinges 30-31, two for each window casement, which are ~~positioned in the upper visible inside area of the casement~~~~the window~~ near the auxiliary levers, ~~as well as on and connect to~~ the frame and the counter-frame and the window casements.

[0036] Every multiple hinge 30-31 consists of two holders 28; 29, two straight elements, ~~which we will call~~or 'wings' 30; 31, and three rotating pins 32; 33; 34, which hold the hinge together. The holders 28; 29 are connected ~~on-at~~ one end to the frame and the window casement. At the other end, the holders have continuous-segmented openings. There are continuous segmented openings ~~on-at~~ both ends of the wings. The holder 28, which is connected to the frame, is connected ~~on-at~~ one end to the wing by a rotating pin 32, which is set into the ~~continuous openings~~a segmented opening. The other end of the ~~so-called~~ wing 31 is connected to the end of the second wing 32 by a second rotating pin 33, which is ~~called-defined here as a~~ central pin and which is ~~set-disposed~~ into the relevant continuous-segmented openings. The other end of the second wing 30 is connected to the other holder 29, which is fixed to the window casement, through a third rotating pin 34, which sits in the relevant continuous

segmented openings. The multiple hinges enable several movement positions, which occur via different axles.

[0037] The rotation of the multiple hinges (which consists of three elementary joints, of which one is fixed firmly to the frame) results in a horizontal movement of the multiple hinges, which is used to open and close the window casement. The force needed for moving the multiple hinges and the window casement, ~~comes from~~ is provided by the auxiliary levers 19, which are put in motion through the drive shaft 16 via the driving motor 17. In addition, the multiple hinges are a mechanical linkage, which – together with the levers – guarantee a movement of the window casements ~~parallel on the level of~~ with the frame.

[0038] During the closing of the window casement, the multiple hinges are ~~compact~~ compacted. During the opening of the ~~same~~ window casement, ~~they~~ the multiple hinges open like a book by positioning themselves at right-angles ~~to the level of~~ to the frame. The ~~straight elements called~~ 'wings', from which the multiple hinges are made, are sufficiently large to enable the window casement to open completely.

[0039] Another mechanical system (Fig 7), which has the same purpose and function as the previous one and which enables the opening and closing of window casements, ~~is built as follows~~ includes two holders, three levers and five joints. Altogether, these components form a 'lever system'. Each 'individual lever' of the previously described system is replaced by a 'lever system', so that every window casement has at least four 'lever systems'. This solution does not require the use of multiple hinges, ~~sledges~~ brackets and guide blocks or swivel-joint roller bearings and profile guides. The main ~~task-object~~ of this mechanical system is to keep the configuration and intended execution of the previous model with the 'individual levers' and to ensure the connection between the individual lever systems through drive shafts, connecting rods, toothed rods, parallel arranged ropes or profile rods. The lever system (Fig 7) consists of a special holder 45, which is fixed to the frame. Inside this device, there is a drive shaft 16, which in turn is inside a sliding bearing, which enables the rotation of the drive shaft in both directions. Near the holder 45, there is the first lever 46 or action lever, which is fixed firmly to the drive shaft, i.e. with the rotating level-plane at a right-angles-angle to the rotation ~~axle~~ axis of the drive shaft. At a specific place of the holder 45, which is fixed to the frame, there is a second lever 47, which is connected ~~on at~~ at one end with the holder through a rotating pin 49. The opposite ends of the action lever 46 and lever 47, which is fixed through a rotating pin 49 with the holder to the

frame, ~~is~~are connected at two different points with a third lever 48 through rotating pins 50; 51. Lever 48, which is connected to other before-mentioned levers, is fixed ~~on~~at one end through a rotating pin 52 to a holder 53 at the window casement. ~~Every-Each~~ drive shaft 16 is connected to two primary or action levers 46 ~~or the action lever~~. The drive shaft 16 itself is connected to an independent driving motor, which is fixed to the frame. All levers in this system are arranged in such a way, that with each rotation of the drive shaft (to which the action lever is firmly fixed) and through the interaction of the levers and their connections, a simultaneous movement of the three levers of this system occurs, through which the third lever (fixed to the window casement) carries out a horizontal ~~feeding~~-motion. ~~In order to keep it simple~~For the sake of simplicity, the lever system described above is called the 'main lever system'.

[0040] Staggered to the main lever system ~~there is~~ an identical lever system, ~~which is called~~identified here as an 'additional lever system' in order to differentiate it from the main lever system. The difference between both systems lies in the fact that the action lever 46 of the additional lever system is – ~~at the one end~~ - fixed to the frame through a rotating pin 24 ~~of across~~ a holder 45. The transfer of movement between the lever systems (the main lever system and the additional lever system) occurs through parallel arranged ropes and/or profile rods 37; 38. The parallel arranged ropes or the profile rods are connected in a suitable position to the action lever 46 of the main lever system and the action lever 46 of the additional lever system through a rotating pin 35; 36. The transfer of ~~the~~ movement between both systems can also occur through connecting rods and toothed rods as shown in the original model with individual levers. The movement of the parallel arranged ropes or profile rods transfers the movement of the action lever of the main lever system ~~at to~~ the relevant ~~actions~~-action lever of the additional lever system.

[0041] This ~~makes~~configuration makes it possible for the movement of the drive shaft (via the drive motor) to create the movement of both action levers, which are connected with the main lever system. This creates a movement around the drive shaft, and the parallel arranged ropes or profile rods move the action lever of the additional lever system, which forwards this movement to its swivel fixed pivot brackets. Every window casement has at least ~~[[4]]~~four lever systems: two main lever systems with drive shafts and two additional lever systems, which are fixed in their ~~relevant~~-holders to the frame or counter-frame of the window casement. The connection of the lever systems through parallel arranged ropes or profile rods enables a ~~feeding~~

motion of the window casement ~~on parallel levels~~ to the frame, ~~which makes~~making it it possible to open and close the window.

ABSTRACT OF THE DISCLOSURE

[0042] The present invention at issue refersrelates to an automatic window system consisting of a frame, two movable window casements, one on the outside and one on the inside of a building, and of a mechanism, which ~~has the characteristic to open and close~~opens and closes the afore-mentioned window casements independently of each other. ~~Specifically, the different physical and optical characteristics of both glass~~Glass panels having certain physical and optical properties may also be included, which is supplemented by as well as a motor-driven blind and a rolled curtain, ~~together with the possibility to determine a variety of positions for both window casements with the help of the described mechanism, is fundamental and important in order to~~ which together regulate the climate and temperature ~~control~~ of the building. ~~In addition, there is a solution specified for the window, which can change~~In one embodiment, the heat flow between the and through the glassed window casementsglass panels can be manipulated.